SAFETY DATA	SHEET (SDS)	-	TECHmix		
Product identifier: TE	ECH-MIX FINISHING ASPHALT				
Date & version: July 10, 20					
	Section 1. Identi	ification			
Product identifier TECH	H-MIX FINISHING ASPHALT				
Other means of identification					
Recommended use and r					
use	č				
Initial supplier identifier	BAUVAL TECH-MIX 3350, Butte-aux-Re	enards, Varennes, Qc (Canada), J32	X 1P7		
	<u>www.tech-mix.com (450) 652-0689</u>				
Emergency telephone number/restriction on use Canada – CANUTEC 24 hour number 613-996-6666					
	Section 2. Hazard id				
	s product (name of the category or subcateg	ory of the hazard class)			
Skin irritation (Category 2)					
Eye irritation (Category 2A)					
Carcinogenicity (Category 1)					
	/ - repeated exposure (Category 1), Organs				
Information elements (sym	bols, signal words, hazard statements and p	precautionary statements of the c	ategory/subcategory)		
P201 Obtain special instruct breathe dusts or mists. P264 P280 Wear gloves/protective If skin irritation occurs: Get IF IN EYES, Rinse cautious P313 If eye irritation persis attention if you feel unwell. I or national regulations.	ans (lungs) through prolonged or repeated explicions before use. P202 Do not handle until all Wash hands/nails/face thoroughly after hand e clothing/eye protection/face protection. P302 medical attention. P362 + P364 Take off cont ely with water for several minutes. Remove co ts: Get medical attention. P308 + P313 IF e P405 Store locked up. P501 Dispose of conten	safety precautions have been read lling. P270 Do not eat, drink or su 2 + P352 IF ON SKIN: Wash with aminated clothing and wash it before ontact lenses, if present and easy to xposed or concerned: Get medica tts/container into safe container in a	noke when using this product. plenty of water. P332 + P313 ore reuse. P305 + P351 + P338 o do. Continue rinsing. P337 + d attention. P314 Get medical		
	Section 3. Composition/inform				
Chemical name (common n	name/synonyms)	CAS number or other	Concentration (%)		
Silica, amorphous, fused		60676-86-0	10-30		
Titanium dioxide		13463-67-7	<1		
Manganese monoxide		1344-43-0	1-5		
Silica-crystalline, Quartz (sat	iiu)	14808-60-7	5-10		
Aluminum oxide		1344-28-1	5-10		
Calcium oxide		1305-78-8	15-40		
Magnesium oxide		1309-48-4	7-13		
Iron trioxide		1309-37-1	15-40		
Fuel oil, no. 2		68476-30-2	1-5		

Asphalt (petroleum)		8052-42-4	1-5	
Section 4. First-aid measures				
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.			
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if			
	victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have			
	victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.			
Skin contact	IF ON SKIN: Wash with plenty of water (15-20 minutes). If skin irritation occurs: Get medical attention. Take off			
	contaminated clothing and wash it before reuse.			
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20 minutes). Remove contact lenses, if present and			
	easy to do. Continue rinsing. If eye irritation persists: Get medical attention.			
Most important symptoms and effects (acute or delayed) Causes skin irritation. Causes serious eye irritation.				
Indication of im	Indication of immediate medical attention/special treatment In all cases, call a doctor. Do not forget this document.			

Product identifier: TECH-MIX FINISHING ASPHALT

Date & version: July 10, 2016 version 1

Section 5. Fire-fighting measures

TECHMI

Specific hazards of the hazardous product (hazardous combustion products)

Carbon oxides and other irritant/toxic gases and fumes.

Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish surrounding products.

Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with cleanup should wear the appropriate protective equipment (See Section 8).

Methods and materials for containment and cleaning up

Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Section 7. Handling and storage

Precautions for safe handling

Wear gloves/protective clothing/eye protection/face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

Section 8. Exposure controls/Personal protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: CAS 60676-86-0 PEL-TWA 0.1 mg/m³; CAS 13463-67-7 ACGIH – TLV-TWA 10 mg/m³ & PEL-TWA 10 mg/m³; CAS 1344-43-0 ACGIH – TLV-TWA 0.2 mg/m³ & PEL-TWA 1 mg/m³ (STEL 3 mg/m³); CAS 14808-60-7 ACGIH – TLV-TWA 0.025 mg/m³ (respirable particles) & PEL-TWA 10 mg/m³ (respirable particles) & 30 mg/m³ (total dust); CAS 1344-28-1 ACGIH – TLV-TWA 1 mg/m³ & PEL-TWA 5 mg/m³ (respirable particles) & 15 mg/m³ (total dust); CAS 1305-78-8 ACGIH – TLV-TWA 2 mg/m³ & PEL-TWA 5 mg/m³; CAS 1309-48-4 ACGIH – TLV-TWA 10 mg/m³ & PEL-TWA 15 mg/m³; CAS 1309-37-1 ACGIH – TLV-TWA 5 mg/m³ & PEL-TWA 10 mg/m³ (respirable particles) & 20 mg/m³ (respirable

Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

Section 9. Physical and chemical properties				
Appearance, physical state/colour Black solid	Vapour pressure Not available			
Odour Petroleum	Vapour density Not available			
Odour threshold Not available	Relative density Not available			
pH Not available	Solubility Insoluble			
Melting/freezing point Not available	Partition coefficient - n- Not available			
	octanol/water			
Initial boiling point/range Not available	Auto-ignition temperature Not available			
Flash point >93°C	Decomposition temperature Not available			
Evaporation rate Not available	Viscosity Not available			
Flammability (solids and Not available	VOC Not available			
gases)				
Upper and lower flammability/explosive limits Not available	Other None known			

Product identifier: TECH-MIX FINISHING ASPHALT Date & version: July 10, 2016 version 1

TECHMIX

Section 10. Stability and reactivity				
Reactivity				
Does not react under the recommended storage and handling conditions prescribed.				
Chemical stability				
Stable under the recommended storage and handling conditions prescribed.				
Possibility of hazardous reactions				
None				
Conditions to avoid (static discharge, shock or vibration)				
None				
Incompatible materials				
Strong oxidizing materials; etc.				
Hazardous decomposition products				
None known				
Section 11. Toxicological information				
Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)				
Causes skin irritation. Causes serious eye irritation. May cause cancer. Causes damage to organs (lungs) through prolonged or repeated	ed			
exposure (inhalation).				
Symptoms related to the physical, chemical and toxicological characteristics				
Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing.				
Delayed and immediate effects (chronic effects from short-term and long-term exposure)				
Skin Sensitization - No data available; Respiratory Sensitization - No data available; Germ Cell Mutagenicity - No data availabl				
Carcinogenicity - Yes, possible according to IARC, ACGIH, NTP or OSHA; Reproductive Toxicity - No data available; Specific Targ	get			
Organ Toxicity — Single Exposure - No data available; Specific Target Organ Toxicity — Repeated Exposure - Possible; Aspiration	on			
Hazard – No data available; Health Hazards Not Otherwise Classified – No data available.				
Numerical measures of toxicity (ATE; LD ₅₀ & LC ₅₀)				
CAS 68476-30-2 LD50 (oral, rat) 12000 mg/kg & LD50 (dermal, rabbit) 4720 µL/kg;				
ATE not available in this document.				
Section 12. Ecological information Ecotoxicity (aquatic and terrestrial information)				
No data available for this product.				
Persistence and degradability No data available				
Bioaccumulative potential No bioaccumulation is to be expected. Mobility in soil No data available				
Other adverse effects No data available				
Section 13. Disposal considerations				
Information on safe handling for disposal/methods of disposal/contaminated packaging				
Dispose of contents/container into safe container in accordance with local, regional or national regulations.	_			
Section 14. Transport information				
UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations				
Not regulated				
UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)				
Not regulated				
UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)				
Not regulated				
Special precautions None				
(transport/conveyance)				
Environmental hazards (IMDG or other) None				
Bulk transport (usually more than 450 L in Possible				
capacity)				

Product identifier: TECH-MIX FINISHING ASPHALT Date & version: July 10, 2016 version 1

TECHMIX

Section 15. Regulatory information				
Safety/health Canadian regulations specifics Refer to Section 2 for the appropriate classification. This product has been classified				
		accordance with the hazard criteria of the Hazardous Products Regulations (HPR).		
Environmental Canadian regulations specifics		Refer to Section 3 for ingredient(s) of the DSL		
	vironmental outside regulations s			
United States OS	SHA information: This product is re	gulated according to OSHA (29 CFR).		
	CSA information: Refer to the ingrea	dients listed in Section 3.		
National Fire Pro	otection Association (NFPA):			
HEALTH: 1		ABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3.		
		Moderate $3 =$ Serious $4 =$ Severe		
California Propo	sition 65: This product contains	chemicals that are known to the State of California to cause cancer or other		
reproductive ha	ırm.			
		Section 16. Other information		
Date of the lates	st revision of the safety data sheet	July 10, 2016 version 1 (NSS ENTREPRISE INC.)		
References	Safety Data Sheets from manufactu	urer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.		
Abbreviations		••••••••••••		
ACGIH	American Conference of Governm	nental Industrial Hygienists		
ATE	Acute toxicity estimate			
CAS	Chemical Abstract Service			
DSL	Domestic Substance List			
IARC	International Agency for Research on Cancer			
IATA	International Air Transport Association			
IMDG	International Maritime Dangerous Goods Code			
LC	Lethal concentration			
LD	Lethal Dosage			
NIOSH	National Institute for Occupational Safety and Health			
NTP	National Toxicology Program (U.S.A.)			
OSHA	Occupational Safety and Health Administration (U.S.A.)			
PEL	Permissible Exposure Limit			
STEL	Short-term Exposure Limit			
TDG	Transport of dangerous goods in Canada			
TLV	Threshold Limit Value			
TSCA	Toxic Substances Control Act			
TWA	Time Weighted Average			
WHMIS To the best of our	Workplace Hazardous Materials I	nformation System herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes		
		of the information contained herein. Final determination of suitability of any material is the sole		
		own hazards and should be used with caution. Although certain hazards are described herein, we		
	hat these are the only hazards that exist.			